



Summary

DW Spectrum Video Management Services is a cloud-managed, cutting-edge approach to surveillance that addresses the primary challenges of managing enterprise-level video while offering actionable, data-driven monitoring at the lowest total cost of deployment on the market.

DW Spectrum Professional is designed for efficiency and optimized control in video management. The service's latest updates make it more efficient, responsive, and user-friendly than ever.

Upgrade to cloud-centric **DW Spectrum Enterprise** and take advantage of cloud-exclusive usability and convenience. Each recording license entitles you to a two-year subscription.

DW Spectrum Pro Features

- · Open architecture / cross-platform
- · Interface is dramatically easier to use
- · Advanced features are standard
- · Cloud connectivity
- · Future-proof infrastructure
- · Al-driven solution

Server

- · Remote log download
- · ONVIF profile selection
- Camera replacement
- Archive encryption
- SSL/TLS for server connections
- · Session-based and multi-factor authentication
- ZFS support
- Intel® quick sync video
- C2P integration
- Dual Stream RTSP/HTTP
- Failover on storage failure
- Layout-as-an-action
- System update

Specifications

| - 1 | | |
|---|--|---|
| Network | | |
| IP protocols | Static, DHCP | |
| Mobile applications | Apple iOS devices, Android smartphones and tablets | |
| ONVIF conformant | Yes | |
| Network connection | 1000 Mbps and higher throughput | |
| Performance | | |
| Camera image control | Control integrated cameras directly from the DW Spectrum client | |
| Version upgrade | In-client upgrade from client | |
| Recording mode | Continuous, motion recording, motion recording + low resolution always, object recording, object + low resolution always, motion & object recording, motion & object + low resolution always | |
| Search modes | Instant motion-based smart search, advanced thumbnail search, calendar search, preview search, frame-by-frame search, object search, advanced object search | |
| Special features | Fully customizable layouts, easy drag-n-drop camera management and recording, video analytics engine support, camera hotspot(link), Failover H.265, H.264, MJPEG, MPEG4 | |
| Compression type | | |
| Pre-alarm recording | Yes USB drive, USB HDD, NAS | |
| External export Video | OSB drive, OSB HDD, NAS | |
| | Voc | |
| Dual-stream recording | Yes Linux* Windows* macQS* (client only.) Apple and Android mobile clients | |
| Operating system | Linux*, Windows*, macOS* (client only), Apple and Android mobile clients | |
| Maximum recommended elements in a single system | Maximum recommended servers in a system: 50* Maximum recommended resources in a system: 10,000* Maximum recommended users in a system: 1000. The maximum number of MEGApix* CaaS™ all-in-one edge cameras in a single system is 30 cameras (all in the same local network, using MEGApix CaaS cameras only). The maximums above are based on lab testing results and could vary significantly based on a project's real-world environment and configuration. | |
| System requirements | Minimum | |
| Operating system | Microsoft Windows Windows 10 Windows 10 Windows Server 2016 Windows Server 2019 Windows Server 2022 **NOTE: DW Spectrum IPVMS for Windows can be installed as a software bundle or the server and client software can be installed separately. Ubuntu (Debian-based Linux) Ubuntu 18.04 LTS "Bionic Beaver" Ubuntu 20.04 LTS: "Focal Fossa" Ubuntu 22.04 LTS: "Jammy Jellyfish" **NOTE: DW Spectrum IPVMS for Ubuntu is only available as separate installations (not bundled). macOS (client only) macOS 10, "11, 112 macOS 12 "Monterey" macOS 13 "Ventura" macOS 14 "Sonoma" **NOTE: Mobile app 22.4 is incompatible with DW Spectrum IPVMS 5.1. **NOTE: Support for Windows 8.1 will be discontinued in DW Spectrum 6.0. | |
| Server Hardware | Systems on Windows 8.1 may not be able Minimum | |
| Processor | Intel® Celeron8th gen processor (or | Intel® Core i5® 8th gen processor (or |
| System RAM | higher) 4GB RAM | higher) 8GB RAM |
| GPU | Support OpenGL 2.1 | Support OpenGL 2.1 |
| Network interface | 2×1Gbps | 2x1Gbps |
| OS Drive | 256GB HDD | Dedicated 256GB SSD or larger |
| Storage Drive | Ensure sufficient read/write capacity to handle camera load | Ensure sufficient read/write capacity to handle camera load |
| Client Desktop Hardware | | Recommended |
| | | Intel® Core i7® 8th gen processor (or |
| Processor | Intel® i5 8th gen processor (or higher) | higher) |
| System RAM | 8GB RAM | 16GB RAM |
| Video card | Integrated Intel® graphics | GeForce® GTX 1650 or better |
| Network interface | 2×1Gbps | 2×1Gbps |
| OS Drive | 256GB HDD | Dedicated 256GB SSD or larger |













Features (cont.)

- Virtual camera (import offline video)
- H.265 support to ONVIF cameras
- Metadata SDK
- Plugins
- Webcam support
- IP camera auto-discovery
- I/O device support
- Device lists (management)
- Support to cameras at every resolution *
- Multi-sensor camera support
- · Server hive architecture
- Cross-platform
- One-click complete system upgrade
- Store anywhere
- Web administration
- · Event rules engines
- · Incredibly lightweight
- Notifications
- One-time recording license charge, fully transferable

Client

- New in Pro! Camera hot spots
- New in Pro! LDAP integration
- New in Pro! Temporary users
- Cross-system layouts
- · Remote log download
- Two-factor authentication
- OS SSL/TLS for Internet connections
- Session-based authentication
- · Independent desktop client updates
- Custom resource groups
- · Video preview thumbnail
- · Audio-video mapping
- 360° panoramic video dewarping
- · Web page proxy
- Client Javascript API
- Native support for DW Ai
- · Chromium browser in-client
- Videowall failover
- Minimum grid size on layouts
- Secure export
- · Custom watermark over video
- · Launch desktop client with CLI
- In-camera analytics
- · Bitrate throttling
- Seamless transition from live to playback

- Watch live and playback video on the same screen
- Easy monitoring
- Enhanced export
- · Web client compatibility
- · Easy bookmark export
- · Archive integrity check
- · Custom camera ID
- · Flex GRID user interface
- Universal fisheye dewarping
- Advanced PTZ
- Region of interest with SpyGlass™
- Smart motion search
- · Adaptive timeline
- Calendar search
- Preview search
- Synchronized or unsynchronized playback
- · Screen record
- · Cloud connect
- · User management
- · Adaptive scaling
- Multi-camera viewing
- · Super lightweight
- Secure and encrypted
- Multi-video export
- Soft triggers
- · Storage analytics
- Showreel
- · Two-way audio
- Text-to-speech event notifications
- · Event rules engine
- · HTTP events and actions
- Bookmarks
- IP intercom device support
- · Image enhancement
- · Event log reports and search
- · Centralized management
- Health monitor
- · System backup and restore
- · Minimize video recording loss
- Audit trail
- · Edge integration
- Videowall
- Help manual

DW Cloud™

- · New in Pro! Emails from the cloud
- Connect directly to any Blackjack® Server
- Complete system and user management
- View live or recorded videos
- Complete system management
- Health monitoring dashboard
- Cloud system merge
- Share access
- Unlimited systems
- Web viewing
- Secure and encrypted
- Cloud API

Mobile

- Push notifications
- Low latency
- Live thumbnails
- Multi-system switching
- Fisheye dewarping
- Secure and encrypted
- PTZ control
- Soft triggers

For developers

- Server API
- Video source SDK
- Storage SDK
- HTTP generic events
- HTTP requests-as-an-action
- Metadata SDK

License Options

| Products | Description | |
|-------------------------------|--------------------------------------|--|
| DW Spectrum* IPVMS Licenses | | |
| DW-SPECTRUMLSC001 | Single recording license | |
| DW-SPECTRUMLSC004 | Four (4) recording licenses | |
| DW-SPECTRUMLSC010 | Ten (10) recording licenses | |
| DW-SPECTRUMLSC020 | Twenty (20) recording licenses | |
| DW-SPECTRUMLSC050 | Fifty (50) recording licenses | |
| DW-SPECTRUMLSC100 | One Hundred (100) recording licenses | |
| Analog Encoder IPVMS Licenses | | |
| DW-SPCP04LSC004 | Four (4) Analog encoder licenses | |
| DW-SPCP16LSC016 | Sixteen (16) Analog encoder licenses | |
| I/O Module IPVMS Licenses | | |
| DW-SPIOLSC001 | Single I/O Module license | |
| Video Wall IPVMS Licenses | | |
| DW-SPVWALL1X2 | Single Video Wall license | |



REV. 07/25







