

NDAA
 COMPLIANT PRODUCT

STAR-LIGHT PLUS™
 Color in Darkness Technology



H.265
 H.264/MJPEG

30fps

2.1MP

Resolution



Intelligent Video Analytics



Star-Light Plus™



2.8, 4.0, 6.0mm Fixed Lens Options



True WDR

5 YEAR

Warranty

Summary

This NDAA-compliant MEGApiX® IP camera provides 2.1MP/1080p resolution at real-time 30fps, includes 2.8, 4.0 and 6.0mm fixed lens options and simultaneous H.265/H.264/MJPEG codec support. The camera is powered by Star-Light Plus™ color in near-total darkness technology for quality video in any lighting conditions, all in an IP67-rated, IK-10 impact resistant ultra low-profile vandal dome housing. All MEGApiX® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP/1080p 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- 2.8mm fixed lens (DWC-MV72Wi28TW, DWC-MPV72Wi28TW)
- 4.0mm fixed lens (DWC-MV72Wi4TW, DWC-MPV72Wi4TW)
- 6.0mm fixed lens (DWC-MV72Wi6TW, DWC-MPV72Wi6TW)
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 80' Smart IR™ with intelligent camera sync
- Ultra low-profile vandal dome camera
- Smart DNR™ 3D digital noise reduction
- True day/night mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- PoE class 2 and DC12V
- UL listed
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- IK 10-rated impact-resistant
- 5 year warranty



Accessories (optional)



DWC-V7CMW
 Ceiling mount bracket



DWC-V7JUNCW
 Junction box





DWC-V7MMW
 Wall mount bracket

DWC-V7DECO
 5x decorative rings

Dimensions

Unit: Inch (mm)



Specifications



IMAGE	
Image sensor	2.1MP/1080p 1/2.8" CMOS
Total pixels	1945 (H) X 1109 (V)
Minimum scene illumination	0.05 lux (color) (DWC-MV72Wi28TW, DWC-MPV72Wi28TW) 0.09 lux (color) (DWC-MV72Wi4TW, DWC-MPV72Wi4TW) 0.05 lux (color) (DWC-MV72Wi6TW, DWC-MPV72Wi6TW) 0.0 lux (B/W)
LENS	
Focal length	2.8mm, F2.0 (DWC-MV72Wi28TW, DWC-MPV72Wi28TW) 4.0mm, F2.6 (DWC-MV72Wi4TW, DWC-MPV72Wi4TW) 6.0mm, F2.0 (DWC-MV72Wi6TW, DWC-MPV72Wi6TW)
Lens type	Fixed lens
HFOV / VFOV	111° / 62° (DWC-MV72Wi28TW, DWC-MPV72Wi28TW) 86° / 46° (DWC-MV72Wi4TW, DWC-MPV72Wi4TW) 55° / 30° (DWC-MV72Wi6TW, DWC-MPV72Wi6TW)
IR distance	80ft range
OPERATIONAL	
Intelligent Video Analytics	I/A: intrusion, line crossing, counting line, loitering, enter, exit, tamper (DWC-MV72Wi28TW, DWC-MV72Wi4TW, DWC-MV72Wi6TW) I/A+: object removed, tailgating, direction, stopped, appear, disappear, object left, logical rules (DWC-MPV72Wi28TW, DWC-MPV72Wi4TW, DWC-MPV72Wi6TW)
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 - 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
3D Digital Noise Reduction	Smart DNR™ 3D-DNR
Wide Dynamic Range (WDR) dB	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail notifications, FTP and SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
NETWORK	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, multi-rate for preview and recording
Bitrate control	Multi streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: Internet Explorer®, Google Chrome®, Mozilla Firefox®, Safari® NOTE: Chrome browser is recommended for IVA configuration
Video management software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% (non-condensing)
IP and IK rating	IP67-rated, IK10 impact-resistant
Other certifications	UL listed, CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC 12V, PoE IEEE 802.3af Class2 (Adapter not included)
Power consumption	DC12V: max 3.7W, PoE: max 5.5W
MECHANICAL	
Material	Aluminum vandal housing, polycarbonate dome
Dimensions	4.13" x 2.4" (105 x 61mm)
Weight	0.79lbs (0.36kg)
Warranty	5 year warranty



Built for Users.™

