


Dimensions

Unit: Inch (mm)



Summary

This NDAA-compliant MEGApix® Pano 5MP 360° view fisheye IP camera with IR can monitor an entire area with a 1.55mm fisheye lens, edge-to-edge image clarity and 5MP images at real-time 30fps, providing ultimate ROI. Star-Light Plus™ color in near-total darkness technology ensures quality video in any lighting condition in an IP66-rated housing, ideal for discrete installations and full room coverage with a single camera.

Features

- 5MP sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- 1.5mm fisheye lens with 360° hemispheric view
- Support 360° hemispheric fisheye view and 360°, 180° and 90° panoramic view
- Edge-to-edge image clarity with no pixel loss
- Simultaneous streaming and multiple codec options for smart bandwidth management
- 360° 80' Smart IR™ with intelligent camera sync for clear B/W images with no need for external light
- Smart DNR™ 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- Two-way audio for direct communication between the monitoring station and the camera's location
- Local SD card slot for local recording in case of network loss
- Web server built-in for easy camera management from any browser
- PoE and DC12V for single cable simplified installation
- NDAA compliant for federal and government projects
- IP66- and IK9-rated camera housing built to last
- 5 year warranty

Accessories (Optional)



DWC-V1CNMW
Corner mount



DWC-VFJUNCW
Junction box



DWC-VFCMW
Ceiling mount bracket



DWC-VFWMW
Wall mount bracket

Specifications



| | |
|--------------------------------|--|
| IMAGE | |
| Image sensor | 6.4MP 1/1.8" CMOS |
| Total pixels | 3096 (H) X 2080 (V) |
| Minimum scene illumination | 0.39 lux (color), 0 lux (B/W) |
| Maximum resolution | 5MP (2592 x 1944) |
| LENS | |
| Focal length | 1.55mm, F2.5 |
| Lens type | Fisheye lens |
| HFOV / VFOV | 185° / 185° |
| IR distance | 80ft range |
| I/O | |
| Audio in / out and compression | 1 (1.0Vrms, 3K ohm) input / 1 output, G.711 |
| Alarm in/out | 1 input/1 output |
| OPERATIONAL | |
| Intelligent Video Analytics | Intrusion, line crossing, counting line, loitering, enter, exit, tamper, object removed, tailgating, direction, stopped, appear, disappear, object left, logical rules.* NOTE: object removed, tailgating, direction, stopped, appear, disappear, object left, and logical rules are available via IVA+ plugin update. For existing cameras, contact your DW sales representative for a complimentary update. |
| Shutter speed | 1/15-1/32000 |
| Slow Shutter | 1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10 |
| Auto gain control | Auto |
| Day / night | Auto, day (color), night (B/W) |
| 3D digital noise reduction | Smart DNR™ 3D-DNR |
| White balance | Yes |
| Mirror and flip | Yes |
| Backlight compensation (BLC) | Yes |
| Privacy zones | 16 programmable privacy masks |
| Alarm notifications | Notifications via e-mail, FTP server or SD card recording |
| Memory slot | Micro SD / SDHC / SDXC (card not included) |
| NETWORK | |
| LAN | RJ45 (10/100Base-T) |
| Video compression type | H.265, H.264, MJPEG |
| Resolution | H.265, H.264: 2592x1944, 2048x1536, 1600x1200, 1280x1024, 800x600, 480x360, 320x240 MJPEG: 1280x1024, 800x600, 480x360, 320x240 |
| Frame rate | Up to 30fps at all resolutions |
| Video bitrate | 100Kbps - 10Mbps, multi-rate for preview and recording |
| Bitrate control | Multi-streaming CBR/VBR at H.265 (controllable frame rate and bandwidth) |
| Streaming capability | Dual-stream at different rates and resolutions |
| IP | IPv4, IPv6 |
| Protocol | TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF |
| Security | HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW) |
| ONVIF conformance | Yes |
| Web viewer | OS: Windows®, Mac® OS, Linux® Browser: IE®, Google Chrome®, Mozilla Firefox®, Safari® NOTE: Chrome browser is recommended for IVA configuration |
| Video management software | DW Spectrum® |
| ENVIRONMENTAL | |
| Operating temperature | -4°F - 122°F (-20°C - 50°C) |
| Operating humidity | Less than 90% (non-condensing) |
| IP and IK rating | IP66-rated, IK9-impact resistant |
| Other certifications | UL listed, CE, FCC, RoHS |
| ELECTRICAL | |
| Power requirement | DC12V, PoE IEEE 802.3af Class3. (Adapter not included) |
| Power consumption | DC12V: max 7.5W, PoE: max 8.7W |
| MECHANICAL | |
| Material | Aluminum vandal fisheye housing |
| Dimensions | 4.9" x 1.88" (125 x 48mm) |
| Weight | 1.1 lbs (0.5kg) |
| Warranty | 5 year warranty |

