


Dimensions
Unit: Inch (mm)



Specifications



IMAGE	
Image sensor	1/2.8" 5.17MP Star-Light Plus™ sensor
Total pixels	2608(H) X 1984(V)
Active pixels	2592(H) X 1944(V)
Minimum scene illumination	0.03 lux (color) 0 lux (white light)
Color temperature	Warm light, 3300K
S/N ratio	50dB
LENS	
Focal length	2.7-12mm F1.3
Lens type	Vari-focal p-iris lens with motorized zoom and auto-focus
Horizontal Field of view (HFOV)	31.5°-89.9°
Vertical Field of view (VFOV)	23.6°-64.5°
LED distance	90' range white light
Optical zoom / digital zoom	4.4x optical zoom
I/O	
Audio input/output	1 microphone built-in/ 1 speaker built-in
Audio compression	G.711 ulaw
Alarm input/output	1 input/1 output
Event trigger	Motion alarm, network loss, temperature anomaly, illegal login, schedule, sensor detection
INTELLIGENT VIDEO ANALYTICS	
Deep learning analytics	Deep Learning object tracking
Analytics filters	Zones and lines, tamper, metadata, intrusion, line crossing, counting, counting lines, appear, disappear, stopped, enter, exit, direction, tailgating, dwell, logical rules
OPERATIONAL	
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 - 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Color only
3D Digital Noise Reduction	Smart DNR™ 3D-DNR
Wide Dynamic Range (WDR)	True WDR
Wide Dynamic Range (WDR) dB	120dB
White balance	Yes
Privacy zones	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Notifications via email, FTP, alarm output, SD card recording and flashlight
Memory slot	Micro SD/SDHC/SDXC class 10 card (not included)
NETWORK	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG H.265: 2592x1944, 2560x1440, 1920x1080, 1280x720, 800x600, 704x576, 704x480, 640x480, 640x360, 352x288, 352x240 H.264: 2592x1944, 2560x1440, 1920x1080, 1280x720, 800x600, 704x576, 704x480, 640x480, 640x360, 352x288, 352x240 MJPEG: 1920x1080, 1280x720, 800x600, 768x432, 704x576, 704x480, 640x480, 640x360, 352x288, 352x240
Resolution	Up to 5MP at all resolutions
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 25Mbps, multi-rate for preview and recording
Bitrate control	Multi-streaming CBR/VBR at H.265 (controllable frame rate and bandwidth)
Streaming capability	Triple Streaming (3rd stream MJPEG only)
IP	IPv4
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: Microsoft Edge®, Google Chrome®, Mozilla Firefox®, Safari®
Video management software	DW Spectrum® IPVMS
Number of DW Spectrum® CaaS™ licenses included	1 DW Spectrum® CaaS™ license included
Local server recording	1TB local memory for recording
Max. number of CaaS™ cameras in the same network/system	Up to 10 MEGAPIX® CaaS™ cameras in the same network/system
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% RH, (non-condensing)
IK rating	IK10 impact-resistant
IP rating	IP67-rated
Other certifications	CE, FCC, UL, NDAA, TAA
ELECTRICAL	
Power requirement	DC12V, PoE IEEE 802.3at Class4 (Adapter not included)
Power consumption	12V DC: 12W, 1A PoE: 15.8W, 3291mA
MECHANICAL	
Material	Aluminum vandal housing, polycarbonate domes
Dimensions	4.92" x 4.79" (125 x 121.7 mm)
Weight	1.94 lbs (0.88 kg)
Warranty	5 year warranty

Summary

This NDAA/TAA-compliant MEGAPIX® Ai CaaS™ all-in-one IP camera provides real-time 30fps 5MP resolution with edge Ai and DW Spectrum® IPVMS server installed and licensed on the camera. No additional server hardware is required. The camera's built-in microphone and speaker, white light and flash LEDs offer high-quality color images and deterrence.

Features & Benefits

- 5MP sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- AI Deep Learning object detection
- Create up to 40 separate detection zones.
- Easy setup with no analytics calibration
- Seamless integration and control with DW Spectrum® IPVMS
- Reduce false alarms with multiple detection zones and logic rules.
- Increase your recording storage with smart recording and no false alarms.
- Built-in 1TB storage options for up to 90 days of retained video*
- Easily to deploy with pre-loaded DW Spectrum IPVMS for out-of-the-box operation.
- 24/7 access to live and recorded video feed
- Automatic installation and licensing with first power on
- 90' white light illumination and red/blue flash LEDs for video, illumination and deterrence in a single camera installation
- Vari-focal p-iris lens with motorized zoom and autofocus for complete remote lens control and focused image any time
- True Wide Dynamic Range (WDR) for clear images in challenging light
- Simultaneous streaming and multiple codec options for smart bandwidth management
- Smart DNR™ 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- Privacy zones cover sensitive areas in the camera's field of view.
- Built-in microphone and speaker for deterrence
- Alarm sensor input and relay output for access control integration
- Web server built-in for easy camera management from any browser
- High-power PoE and DC12V for single cable simplified installation
- NDAA/TAA compliant for federal and government projects
- IP67- and IK10-rated camera housing built to last
- 5 year warranty

Accessories (Optional)



Built for Users.™



866.446.3595

sales@digital-watchdog.com

www.digital-watchdog.com