




Dimensions
unit: Inch (mm)



- 5MP**
at 20fps
- Universal HD / Analog
- Star-Light Plus™
- 2.7-13.5mm
Vari-focal P-Iris Lens
- WDR
- 5 YEAR**
Warranty

Summary

Featuring Star-Light Plus™ color in near-total darkness, 5MP Star-Light Plus™ Universal HD over Coax® cameras are NDAA compliant and deliver crystal-clear images and support HD-Analog, HD-TVI and HD-CVI. The weather resistant vandal dome cameras are IP66 rated and can be controlled via the same coax cable using UTC. All DW® Universal HD over Coax® cameras are engineered to work with our VMAX® A1 Plus™ DVRs using your existing coax infrastructure for a cost effective, high resolution surveillance solution.

Features

- Universal HD over Coax® technology with HD-Analog, HD-TVI, HD-CVI
- Star-Light™ color in near-total darkness technology
- 1/2.8" image sensor
- 5MP at 20fps, 4MP at real-time 30fps
- 2.7-13.5mm vari-focal p-iris lens
- True wide dynamic range (WDR)
- OSD control via coaxial (UTC)
- CleanView™ hydrophobic dome coating repels water, dust and grease
- 100' Smart IR™ with intelligent camera sync.
- Smart DNR™ 3D digital noise reduction
- True day/night mechanical IR cut filter
- De-Fog™ extreme weather image compensation
- Auto sensing 24VAC/12VDC with line lock
- Easy icon driven OSD menu with built-in joystick
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- 1 alarm output
- IP66 environmental-rated dust-tight and water-resistant
- IK 10-rated impact-resistant
- NDAA compliant
- 5 year warranty

Specifications

IMAGE	
Image sensor	5MP 1/2.8" CMOS
Active pixels	2608(H) x 1960(V)
Scanning system	Progressive scan
Frequency	60Hz / 50Hz
Signal technology	Universal HD over Coax® technology with HD-Analog, HD-TVI, HD-CVI to 5MP
Synchronization	Internal
Resolution	2592(H) x 1944(V)
Minimum scene illumination	0.08 lux (color) 0 lux (B/W)
Video output	HD-Analog and HD-TVI: 5MP/1944p @ 20fps HD-Analog, HD-TVI and HD-CVI: 4MP/1440p @ 30fps CVBS output for video testing
2nd video output	CVBS output for video testing
I/O	
Alarm output	1 alarm output
LENS	
Focal length	2.7 - 13.5mm
Lens type	Vari-focal p-iris lens
Field of view (FoV)	102° - 31.4°
IR distance	100ft range
OPERATIONAL	
Shutter mode	Auto
Shutter speed	1/30-1/30,000
Backlight (BLC)	Yes
Star-Light (sense-up)	Off - x32
Wide Dynamic Range (WDR)	Double shutter WDR, 120dB
Smart DNR™ noise reduction	3D/2D DNR
White balance	Yes
Day/night	Auto, day (color), night (B/W)
Mirror/flip	Yes
Auto gain control	Max 72dB
Motion detection	Yes
Privacy zones	Yes
Sharpness	Yes
Gamma	0.45
De-fog	Yes
RS485/UTP built-in	Pelco D/UTC
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% RH (non-condensing)
IP rating	IP66-rated
IK rating	IK 10-rated impact-resistant
Other certifications	FCC, CE, ROHS
ELECTRICAL	
Power requirements	DC12V/AC24V dual voltage
Power consumption	DC12V(LED OFF): 3.3W (275mA) DC12V(LED ON): 5.9W (495mA) AC24V(LED OFF): 2.75W (200mA) AC24V(LED ON): 5.3W (360mA)
MECHANICAL	
Material	Aluminum vandal housing, polycarbonate dome
Dimensions	5.7" x 4.26" (145 x 108.3 mm)
Weight	1.98lbs (0.9kg)
Warranty	5 year warranty

Accessories (Optional)



Increase sales and profitability. Sign up and become a DW Channel Partner today!



☎ : 866.446.3595 ✉ : sales@digital-watchdog.com 🌐 : www.digital-watchdog.com

